

Environmental Product Declaration (EPD)  
According to ISO 14025 and EN  
15804+A2:2019

# GIS air termination T155-7g

Registration number:	EPD-Kiwa-EE-202490-EN
Issue date:	27-05-2025
Valid until:	27-05-2030
Declaration owner:	Grid Solutions
Publisher:	Kiwa-Ecobility Experts
Programme operator:	Kiwa-Ecobility Experts
Status:	verified



## 1 General information

### 1.1 PRODUCT

GIS air termination T155-7g

### 1.2 REGISTRATION NUMBER

EPD-Kiwa-EE-202490-EN

### 1.3 VALIDITY

**Issue date:** 27-05-2025

**Valid until:** 27-05-2030

### 1.4 PROGRAMME OPERATOR

Kiwa-Ecobility Experts  
Wattstraße 11-13  
13355 Berlin  
DE



Raoul Mancke

(Head of programme operations, Kiwa-Ecobility Experts)



Dr. Ronny Stadie

(Verification body, Kiwa-Ecobility Experts)

### 1.5 OWNER OF THE DECLARATION

**Manufacturer:** Grid Solutions

**Address:** 167 QUAI de la bataille de stalingrad , 92130 Issy-les-Moulineaux, France

**E-mail:** Solene.Michaud@gevernova.com

**Website:** www.gevernova.com/grid-solutions

**Production location:** Grid Solutions

**Address production location:** 1 rue Paul Doumer , 73 106 Aix-les-Bains, France

### 1.6 VERIFICATION OF THE DECLARATION

The independent verification is in accordance with the ISO 14025:2011. The LCA is in compliance with ISO 14040:2006 and ISO 14044:2006. The EN 15804+A2:2019 serves as the core PCR.

☐ Internal ☒ External



Elisabeth Amat Guasch, Greenize

### 1.7 STATEMENTS

The owner of this EPD shall be liable for the underlying information and evidence. The programme operator Kiwa-Ecobility Experts shall not be liable with respect to manufacturer data, life cycle assessment data and evidence.

### 1.8 PRODUCT CATEGORY RULES

Kiwa-Ecobility Experts, General Programme Instructions "Product Level", SOP EE 1203\_R. 2.0

Kiwa-Ecobility Experts, General Programme Instructions "Product Level" – Annex B1 Environmental Information Programme according to EN 15804 / ISO 21930, SOP EE 1203\_R. 2.0

EPDItaly007 Core Product Category Rules based on EN 50693 for electrical and electronic products Rev. 3.1

EPDItaly 010:PCR Part B for insulator. Rev. 1

# 1 General information

## 1.9 COMPARABILITY

In principle, a comparison or assessment of the environmental impacts of different products is only possible if they have been prepared in accordance with EN 15804+A2:2019. For the evaluation of the comparability, the following aspects have to be considered in particular: PCR used, functional or declared unit, geographical reference, the definition of the system boundary, declared modules, data selection (primary or secondary data, background database, data quality), scenarios used for use and disposal phases, and the life cycle inventory (data collection, calculation methods, allocations, validity period). PCRs and general program instructions of different EPD program operators may differ. Comparability needs to be evaluated. For further guidance, see EN 15804+A2:2019 and ISO 14025.

## 1.10 CALCULATION BASIS

**LCA method R<THINK:** Ecobility Experts | EN15804+A2

**LCA software\*:** Simapro 9.6

**Characterization method:** R<THINK characterization method (see references for more details)

**LCA database profiles:** ecoinvent ( version - 3.9.1)

**Version database:** v3.9.1 (20250306)

*\* Simapro is used for calculating the characterized results of the Environmental profiles within R<THINK.*

## 1.11 LCA BACKGROUND REPORT

This EPD is generated on the basis of the LCA background report 'GIS air termination T155-7g' with the calculation identifier ReTHiNK-102490.

## 2 Product

### 2.1 PRODUCT DESCRIPTION

GE Vernova's GIS/air termination is an insulator forming a passage for a conductor through a non-insulating partition. It allows to move from pressurized gas insulation medium (g3) to atmospheric air. For temperature down to -25°C.

The constituent materials of GIS air termination T155 is given in the table below.

Materials	Weight (kg)	Percentage(%)
Aluminium and its alloys	228.0	40.99
Copper and its alloys	52.0	9.35
Stainless steel	22	3.95
Steel low-alloyed	3.0	0.54
PolyPropylene (PP)	0.6	0.11
PolyAmide (PA)	0.5	0.09
PolyEthyleneTerephthalate (PET)	0.3	0.05
Polymethylmethacrylate (PMMA)	0.2	0.04
EPDM	0.6	0.11
Other elastomers	1.1	0.20
Silicone	134.0	24.9
Other duromers	90.0	16.18
Epoxy resin (EP)	14.0	2.52
Refrigerant gases and others	8.9	1.80
<b>Total</b>	<b>555.2</b>	<b>100</b>

The constituent materials of the packaging and accessories are presented below.

Materials	Amount (kg)
Plywood	67.944
PE (Polyethylene)	0.185
PP (Polypropylene)	0.085
PU (Polyurethane), proxy for foam	0.027

Materials	Amount (kg)
PVC (Polyvinyl Chloride), proxy for tape	0.014
Sawn wood	40.592
Steel (screw)	0.37
<b>Total</b>	<b>108.886</b>

### 2.2 APPLICATION (INTENDED USE OF THE PRODUCT)

The GIS/air termination from GE Vernova can be used in power transmission and distribution, including integration of renewable energy, offshore/onshore wind connections, large power plants, industry applications, and long-range power transmission.

### 2.3 REFERENCE SERVICE LIFE

#### RSL PRODUCT

In accordance with PCR EPDItaly 010: Part B for Insulators, the Reference Service Life (RSL) for the use stage is defined as 20 years. However, the manufacturer indicates that, based on the provisions of IEC 62271-320 *High-voltage switchgear and controlgear – Part 320: Type tests for high-voltage switchgear and controlgear*, the product may have an operational lifespan of up to 40 years.

#### USED RSL (YR) IN THIS LCA CALCULATION:

20

#### RSL PARTS

-

Description	Material	RSL [yr]
<i>Maintenance (B2)</i>		
g3 leakage during use phase	g3	1

### 2.4 TECHNICAL DATA

Electrical characteristics of T155-7g are given in Table below.

## 2 Product

Characteristics	Units	Value
Rated Voltage	kVms	420
Rated nominal current	Ams	5000
Rated frequency	Hz	50/60


### 2.5 SUBSTANCES OF VERY HIGH CONCERN

According to manufacture, no substance present in the product with a concentration exceeding 0.1% of the total weight is included on the "List of Substances of Very High Concern" (SVHC) for authorization under REACH legislation.

### 2.6 DESCRIPTION PRODUCTION PROCESS

The product is manufactured using a variety of raw materials, including steel, aluminum, silicon, plastics, elastomers, durometers, and copper alloys. Component production takes place at external suppliers through processes such as machining and injection molding. These components are then transported by truck to the assembly facility located in France. At the French factory, the final product is assembled through mechanical operations such as fixing and screwing. The assembled units are packaged using wooden

boxes and plastic protective materials before being prepared for delivery to the installation site. The energy consumption is calculated based on measured data from factory in France.



### 2.7 CONSTRUCTION DESCRIPTION

Construction is declared to account for the environmental impacts associated with the end-of-life packaging.

### 3 Calculation rules

#### 3.1 FUNCTIONAL UNIT

##### 1 piece

1 piece of product (Gas Insulated Substation air termination T155-7g)

Reference unit: piece (p)

#### 3.2 CONVERSION FACTORS

Description	Value	Unit
Reference unit	1	p
Weight per reference unit	555.200	kg
Conversion factor to 1 kg	0.001801	p

#### 3.3 SCOPE OF DECLARATION AND SYSTEM BOUNDARIES

This is a Cradle to grave EPD. The life cycle stages included are as shown below:

(X = module included, ND = module not declared)

A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

The modules of the EN 15804 contain the following:

Module A1 = Raw material supply	Module B5 = Refurbishment
Module A2 = Transport	Module B6 = Operational energy use
Module A3 = Manufacturing	Module B7 = Operational water use
Module A4 = Transport	Module C1 = De-construction / Demolition
Module A5 = Construction - Installation process	Module C2 = Transport
Module B1 = Use	Module C3 = Waste Processing
Module B2 = Maintenance	Module C4 = Disposal
Module B3 = Repair	Module D = Benefits and loads beyond the product system boundaries
Module B4 = Replacement	

#### 3.4 REPRESENTATIVENESS

This EPD is representative for GIS air termination T155-7g, a product of Grid Solutions . The results of this EPD are representative for European Union.

#### 3.5 CUT-OFF CRITERIA

##### Product stage (A1-A3)

All input flows (e.g. raw materials, transportation, energy use, packaging, etc.) and output flows (e.g. production waste) are considered in this LCA. The total neglected input flows do therefore not exceed the limit of 5% of energy use and mass.

##### Construction process stage (A4-A5)

### 3 Calculation rules

All input flows (e.g. transportation to the construction site, additional raw material use for construction, installation energy (use) of energy use for assembly, etc.) and output flows (e.g. construction waste, packaging waste, etc.) are considered in this LCA. The total neglected input flows do therefore not exceed the limit of 5% of energy use and mass.

#### Use stage (B2)

The product is a passive component that does not require energy, water, or replacement during its service life. Therefore, Modules B1, B3, B4, B5, B6, and B7 are considered as not relevant. Module B2 (maintenance) is included to account for potential gas leakage during the use phase.

All (known) input flows (e.g. raw materials, transportation, energy use, packaging, etc.) and output flows (e.g. emissions to soil, air and water, construction waste, packaging waste, end-of-life waste, etc.) related to the building fabric are considered in this LCA. The total neglected input flows do therefore not exceed the limit of 5% of energy use and mass.

#### End of life stage (C1-C4)

All input flows (e.g. energy use for demolition or disassembly, transport to waste processing, etc.) and output flows (e.g. end-of-life waste processing of the product, etc.) are considered in this LCA. The total neglected input flows do therefore not exceed the limit of 5% of energy use and mass.

For demolition, the energy consumption associated with deconstruction or dismantling is calculated in accordance with the Product Environmental Footprint Category Rules (PEFCRs) for Building Products (2019).

Assumption for the demolition at EoL	Amount per kg of demolished material	Unit	Data set	Database
Diesel consumption in construction machine	0.0437	MJ/kg	Thermal energy from light fuel oil	Sphera

#### Benefits and loads beyond the system boundary (Module D)

All benefits and loads beyond the system boundary resulting from reusable products, recyclable materials and/or useful energy carriers leaving the product system are considered in this LCA.

#### Excluded Elements from LCA Calculation:

The transport of personnel to the plant;

The transportation of personnel within the plant;

Research and development activities;

Long-term emissions.

### 3.6 ALLOCATION

Allocations were avoided as far as possible. No by-products or co-products are produced during the manufacture of the analysed product. The energy requirements of production were allocated to the individual products on the basis of energy consumption measurements. Specific information on the allocations within the background data can be found in the documentation of the Ecoinvent datasets.

### 3.7 DATA COLLECTION & REFERENCE PERIOD

All primary data were collected by manufacture of product for the reference year of 2023 covering the period from January to December 2023.

### 3.8 ESTIMATES AND ASSUMPTIONS

· Due to the large number of suppliers and associated data limitations, transport has been modeled using generic profiles representative of typical supply chains where specific data was not available. A company-specific transport profile has been applied to reflect realistic sourcing practices. The following assumptions apply:

1. Domestic sourcing (within France): Transported 1,000 km by freight lorry, 16–32 metric tons, EURO 6, diesel.
2. European sourcing (EU): Transported 3,500 km by freight lorry, 16–32 metric tons, EURO 6, diesel.



## 3 Calculation rules

3. Global sourcing: Shipped 19,000 km by sea freight (oceanic container ship, heavy fuel oil) and transported a further 1,000 km by freight lorry, 16–32 metric tons, EURO 4, diesel.

- The G3 insulation gas consists of a C<sub>4</sub>F<sub>7</sub>N / O<sub>2</sub> / CO<sub>2</sub> mixture. This gas has been modelled separately based on the manufacturer's data and in accordance with the Grid Solutions harmonized standard document NT312440.
- C<sub>4</sub>F<sub>7</sub>N production has been modeled using assumptions and secondary data, including proxy datasets from Ecoinvent. Results may differ from actual industrial production.
- A payload factor of 50 percent was used for all truck transports, which in fact corresponds to a full delivery and empty return trip. A data set for a non-specific truck was used.
- During the demolition phase, a 0.09% leakage rate of g3 gas is assumed. This amount has been calculated and considered in the emissions calculation.
- For the end-of-life scenario, the End of life default scenarios suggested in IEC/TR 62635 (Annex D.3) are used.
- Module A4 (Transport) is calculated based on the assumption that the product is transported over a distance of 2,600 km from the factory in Aix-les-Bains, France, to Bergen, Norway. The transportation is assumed to involve a combination of road and sea freight, using the following datasets:

1. Transport, freight, lorry, unspecified {RER} | market for transport, freight, lorry, unspecified | Cut-off, U
2. Transport, freight, sea, container ship {GLO} | market for transport, freight, sea, container ship | Cut-off, U

- The product is a passive component that does not require energy, water, or replacement during its service life. Therefore, Modules B1, B3, B4, B5, B6, and B7 are considered as not relevant. Module B2 (maintenance) is included to account for potential gas leakage during the use phase.
- Gas leakage during the use phase (B2 – Maintenance) has been calculated in the model and represents 0.5% of the total gas mass.

- The A5 (Installation) is declared to account for the environmental impacts associated with the end-of-life of packaging.

### 3.9 DATA QUALITY

Both primary and secondary data have been used. All primary data were collected by the product manufacturer for the reference year 2023, covering the period from January to December. The main source of primary data is the bill of materials, supplemented by factory-specific data provided by the manufacturing facility in France.

For the data, which was needed for modelling but was not provided by the manufacturer and could not be influenced by them, generic data was used. Secondary data were sourced from the regularly updated Ecoinvent database (version 3.9.1), aligning with EN 15804 standards to ensure background data not exceeding 10 years.

ReTHiNK EPD web application was used to model the life cycle for the production and disposal of the declared product systems. To ensure that the results are comparable, consistent background data from the international database Ecoinvent was used in the LCA (e.g. data records on energy, transport, auxiliary materials, and suppliers). Almost all consistent data sets contained in the Ecoinvent database are documented and can be viewed online.

The scenarios included are currently in use and are representative for one of the most likely scenario alternatives. According to the criteria of the “UN Environmental Global Guidance on LCA database development” mentioned in EN 15804+A2, the data quality for all three representativeness categories (geographical, technical and time) can be described as good.

### 3.10 POWER MIX

With regard to the energy consumption, a "market-based approach" was used. Electricity supply is based on the French national residual grid mix, using the dataset "Electricity, medium voltage {FR} | electricity, medium voltage, residual mix. This mix has a total Global Warming Potential (GWP) of 0.0813 kg CO<sub>2</sub> eq. per kWh.



## 4 Scenarios and additional technical information

### 4.1 TRANSPORT TO CONSTRUCTION SITE (A4)

For the transport from production place to assembly/user, the following scenario is assumed for module A4 of this EPD.

	Value and unit
Vehicle type used for transport	Transport for installation (lorry & Sea)
Fuel type and consumption of vehicle	not available
Distance	2650 km
Capacity utilisation (including empty returns)	50 % (loaded up and return empty)
Bulk density of transported products	inapplicable
Volume capacity utilisation factor	1

### 4.2 ASSEMBLY (A5)

The following information describes the scenarios for flows entering the system and flows leaving the system at module A5.

#### FLOWS ENTERING THE SYSTEM

For flows entering the system at A5 the following scenario is assumed for module A5.

	Value	Unit
<i>Energy consumption for installation/assembly</i>		
(ei3.9.1) Diesel, burned in machine (incl. emissions)	0.6107	l

#### FLOWS LEAVING THE SYSTEM

The following output flows leaving the system at module A5 are assumed.

Description	Value	Unit
Output materials as result of loss during construction	3	%
Output materials as result of waste processing of materials used for installation/assembly at the building site	0.000	kg
Output materials as result of waste processing of used packaging	108.886	kg

### 4.3 USE STAGE (B1)

No significant environment impact in the use stage modules, because there is no (significant) emission to air, soil or water.

## 4 Scenarios and additional technical information

### 4.4 MAINTENANCE (B2)

Technical maintenance is needed during Use Stage. For maintenance the scenario(s) as mentioned below are included in this EPD.

Description	Service cycle (yr)	Number of cycles (n)	Amount per cycle	Total Amount	Unit
g3 leakage during use phase	1	19	0.0445	0.8455	kg

### 4.5 REPAIR (B3)

Repairs are not applicable within the functional unit and to achieve the reference service life.

### 4.6 OPERATIONAL ENERGY USE (B6)

Description	Service cycle (yr)	Number of cycles (n)	Amount per cycle	Total Amount	Unit
-------------	--------------------	----------------------	------------------	--------------	------

### 4.7 OPERATIONAL WATER USE (B7)

Description	Service cycle (yr)	Number of cycles (n)	Amount per cycle	Total Amount	Unit
-------------	--------------------	----------------------	------------------	--------------	------

### 4.8 DE-CONSTRUCTION, DEMOLITION (C1)

The following information describes the scenario for demolition at end of life.

Description	Amount	Unit
(ei3.9.1) Diesel, burned in machine (incl. emissions)	0.611	l
g3	0.008	kg

### 4.9 TRANSPORT END-OF-LIFE (C2)

The following distances and transport conveyance are assumed for transportation during end of life for the different types of waste processing.

## 4 Scenarios and additional technical information

Waste Scenario	Transport conveyance	Not removed (stays in work) [km]	Landfill [km]	Incineration [km]	Recycling [km]	Re-use [km]
Steel waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
Aluminium waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
Copper waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
PE waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
PET waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
PMMA waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
Epoxy resin	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
Other duromers	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
EPDM	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0
Gas g3 waste scenario	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)	0	100	150	50	0

The transport conveyance(s) used in the scenario(s) for transport during end of life has the following characteristics.

	Value and unit
Vehicle type used for transport	(ei3.9.1) Lorry (Truck), unspecified (default)   market group for (GLO)
Fuel type and consumption of vehicle	not available
Capacity utilisation (including empty returns)	50 % (loaded up and return empty)

## 4 Scenarios and additional technical information

Bulk density of transported products	inapplicable
Volume capacity utilisation factor	1

### 4.10 END OF LIFE (C3, C4)

The scenario(s) assumed for end of life of the product are given in the following tables.  
First the assumed percentages per type of waste processing are displayed, followed by the assumed amounts.

Waste Scenario	Region	Not removed (stays in work) [%]	Landfill [%]	Incineration [%]	Recycling [%]	Re-use [%]
Steel waste scenario	EU	0	6	0	94	0
Aluminium waste scenario	EU	0	9	3	91	0
Copper waste scenario	EU	0	15	0	85	0
PE waste scenario	EU	0	9	1	90	0
PET waste scenario	EU	0	95	5	0	0
PMMA waste scenario	EU	0	30	70	0	0
Epoxy resin	EU	0	95	5	0	0
Other duromers	EU	0	30	70	0	0
EPDM	EU	0	30	70	0	0
Gas g3 waste scenario	EU	1	0	39	60	0

Waste Scenario	Not removed (stays in work) [kg]	Landfill [kg]	Incineration [kg]	Recycling [kg]	Re-use [kg]
Steel waste scenario	0.000	1.500	0.000	23.500	0.000
Aluminium waste scenario	0.000	20.520	6.840	207.480	0.000
Copper waste scenario	0.000	7.800	0.000	44.200	0.000
PE waste scenario	0.000	0.054	0.006	0.540	0.000
PET waste scenario	0.000	0.760	0.040	0.000	0.000
PMMA waste scenario	0.000	0.060	0.140	0.000	0.000
Epoxy resin	0.000	140.600	7.400	0.000	0.000
Other duromers	0.000	27.330	63.770	0.000	0.000
<b>Total</b>	<b>0.089</b>	<b>198.804</b>	<b>82.087</b>	<b>281.060</b>	<b>0.000</b>

## 4 Scenarios and additional technical information

Waste Scenario	Not removed (stays in work) [kg]	Landfill [kg]	Incineration [kg]	Recycling [kg]	Re-use [kg]
EPDM	0.000	0.180	0.420	0.000	0.000
Gas g3 waste scenario	0.089	0.000	3.471	5.340	0.000
<b>Total</b>	<b>0.089</b>	<b>198.804</b>	<b>82.087</b>	<b>281.060</b>	<b>0.000</b>

### 4.11 BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARY (D)

The presented Benefits and loads beyond the system boundary in this EPD are based on the following calculated Net output flows in kilograms and Energy recovery displayed in MJ Lower Heating Value.

Waste Scenario	Net output flow [kg]	Energy recovery [MJ]
Steel waste scenario	12.831	0.000
Aluminium waste scenario	39.079	0.000
Copper waste scenario	44.200	0.000
PE waste scenario	0.540	0.197
PET waste scenario	0.000	1.114
PMMA waste scenario	0.000	4.311
Epoxy resin	0.000	203.726
Other duromers	0.000	1703.297
EPDM	0.000	11.218
Gas g3 waste scenario	5.340	0.000
<b>Total</b>	<b>101.990</b>	<b>1923.862</b>

## 5 Results

For the impact assessment long-term emissions (>100 years) are not considered. The results of the impact assessment are only relative statements that do not make any statements about end-points of the impact categories, exceedance of threshold values, safety margins or risks. The following tables show the results of the indicators of the impact assessment, of the use of resources as well as of waste and other output flows.

### 5.1 ENVIRONMENTAL IMPACT INDICATORS PER PIECE

#### CORE ENVIRONMENTAL IMPACT INDICATORS EN 15804+A2

Abbr.	Unit	A1	A2	A3	A1- A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-total	kg CO <sub>2</sub> eq.	4.06E+3	7.17E+1	2.07E+2	4.34E+3	2.48E+2	3.22E+2	0.00E+0	4.67E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.58E+0	6.89E+0	2.94E+2	2.02E+1	-1.08E+3
GWP-f	kg CO <sub>2</sub> eq.	4.12E+3	7.16E+1	3.49E+2	4.54E+3	2.48E+2	1.60E+2	0.00E+0	4.67E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.58E+0	6.86E+0	2.93E+2	2.01E+1	-1.07E+3
GWP-b	kg CO <sub>2</sub> eq.	-6.45E+1	2.21E-2	-1.43E+2	-2.08E+2	8.19E-2	1.62E+2	0.00E+0	1.17E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	4.03E-4	2.24E-3	2.44E-1	1.25E-2	-5.39E-1
GWP-luluc	kg CO <sub>2</sub> eq.	7.51E+0	3.41E-2	5.18E-1	8.06E+0	1.21E-1	2.59E-1	0.00E+0	5.33E-3	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.88E-4	2.45E-2	6.21E-2	2.44E-3	-2.66E+0
ODP	kg CFC 11 eq.	2.48E-4	3.24E-6	7.41E-6	2.59E-4	5.42E-6	1.36E-5	0.00E+0	2.01E-7	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	3.57E-8	1.22E-7	1.60E-6	5.90E-8	-5.07E-3
AP	mol H <sup>+</sup> eq.	5.44E+1	2.07E-1	1.05E+0	5.56E+1	1.18E+0	1.81E+0	0.00E+0	2.60E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.03E-2	3.29E-2	3.11E-1	2.05E-2	-3.93E+1
EP-fw	kg P eq.	2.75E-1	6.31E-4	1.21E-2	2.88E-1	2.03E-3	8.94E-3	0.00E+0	2.23E-4	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	9.66E-6	6.83E-5	1.56E-3	5.81E-5	-1.13E-1
EP-m	kg N eq.	4.76E+0	5.45E-2	3.52E-1	5.16E+0	4.61E-1	1.98E-1	0.00E+0	4.06E-3	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	9.34E-3	1.25E-2	6.25E-2	1.39E-2	-1.85E+0
EP-T	mol N eq.	5.82E+1	5.81E-1	3.94E+0	6.27E+1	4.98E+0	2.34E+0	0.00E+0	4.53E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.02E-1	1.33E-1	7.07E-1	7.46E-2	-2.49E+1

**GWP-total**=Global Warming Potential total (GWP-total) | **GWP-f**=Global Warming Potential fossil fuels (GWP-fossil) | **GWP-b**=Global Warming Potential biogenic (GWP-biogenic) | **GWP-luluc**=Global Warming Potential land use and land use change (GWP-luluc) | **ODP**=Depletion potential of the stratospheric ozone layer (ODP) | **AP**=Acidification potential, Accumulated Exceedance (AP) | **EP-fw**=Eutrophication potential, fraction of nutrients reaching freshwater end compartment (EP-freshwater) | **EP-m**=Eutrophication potential, fraction of nutrients reaching marine end compartment (EP-marine) | **EP-T**=Eutrophication potential, Accumulated Exceedance (EP-terrestrial) | **POCP**=Formation potential of tropospheric ozone (POCP) | **ADP-mm**=Abiotic depletion potential for non fossil resources (ADP mm) | **ADP-f**=Abiotic depletion for fossil resources potential (ADP fossil) | **WDP**=Water (user) depreciation potential, deprivation-weighted water consumption (WDP)

## 5 Results

Abbr.	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
	kg																		
POCP	NMVOC	3.97E+1	2.77E-1	2.23E+0	4.22E+1	1.73E+0	1.41E+0	0.00E+0	1.80E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	3.01E-2	4.55E-2	2.24E-1	2.99E-2	-7.93E+0
	eq.																		
ADP-mm	kg Sb-eq.	4.87E-1	2.30E-4	-1.63E-3	4.85E-1	7.69E-4	1.52E-2	0.00E+0	5.18E-5	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.20E-6	2.15E-5	1.48E-3	6.13E-6	-4.75E-1
ADP-f	MJ	5.09E+4	1.02E+3	1.25E+4	6.44E+4	3.57E+3	2.15E+3	0.00E+0	1.09E+2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.93E+1	9.83E+1	5.51E+2	5.73E+1	-1.09E+4
	m3 world																		
WDP	eq.	1.81E+3	4.48E+0	1.99E+2	2.01E+3	1.55E+1	6.27E+1	0.00E+0	2.27E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	8.07E-2	5.37E-1	8.21E+0	2.13E+0	-4.50E+2

**GWP-total**=Global Warming Potential total (GWP-total) | **GWP-f**=Global Warming Potential fossil fuels (GWP-fossil) | **GWP-b**=Global Warming Potential biogenic (GWP-biogenic) | **GWP-luluc**=Global Warming Potential land use and land use change (GWP-luluc) | **ODP**=Depletion potential of the stratospheric ozone layer (ODP) | **AP**=Acidification potential, Accumulated Exceedance (AP) | **EP-fw**=Eutrophication potential, fraction of nutrients reaching freshwater end compartment (EP-freshwater) | **EP-m**=Eutrophication potential, fraction of nutrients reaching marine end compartment (EP-marine) | **EP-T**=Eutrophication potential, Accumulated Exceedance (EP-terrestrial) | **POCP**=Formation potential of tropospheric ozone (POCP) | **ADP-mm**=Abiotic depletion potential for non fossil resources (ADP mm) | **ADP-f**=Abiotic depletion for fossil resources potential (ADP fossil) | **WDP**=Water (user) depreciation potential, deprivation-weighted water consumption (WDP)

### ADDITIONAL ENVIRONMENTAL IMPACT INDICATORS EN 15804+A2

Abbr.	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PM	disease incidence	2.90E-4	5.40E-6	1.96E-5	3.15E-4	2.42E-5	1.15E-5	0.00E+0	2.22E-7	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	5.62E-7	6.78E-7	4.59E-6	4.01E-7	-1.24E-4
IR	kBq U235 eq.	1.15E+2	9.84E-1	8.94E+1	2.06E+2	1.84E+0	6.36E+0	0.00E+0	3.21E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	8.66E-3	3.84E-2	1.37E+0	4.70E-2	-1.32E+1
ETP-fw	CTUe	6.25E+4	4.80E+2	1.75E+3	6.48E+4	1.76E+3	2.14E+3	0.00E+0	3.33E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.37E+1	7.26E+1	8.03E+2	3.78E+2	-2.52E+4
HTP-c	CTUh	9.69E-6	3.15E-8	7.01E-7	1.04E-5	1.33E-7	5.28E-7	0.00E+0	4.21E-9	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	6.96E-10	3.64E-9	7.05E-8	2.05E-9	-6.60E-6
HTP-nc	CTUh	5.28E-4	7.13E-7	-1.64E-6	5.27E-4	2.76E-6	1.67E-5	0.00E+0	8.58E-8	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	5.32E-9	7.90E-8	1.88E-6	6.14E-8	-5.36E-4

**PM**=Potential incidence of disease due to PM emissions (PM) | **IR**=Potential Human exposure efficiency relative to U235 (IRP) | **ETP-fw**=Potential Comparative Toxic Unit for ecosystems (ETP-fw) | **HTP-c**=Potential Comparative Toxic Unit for humans (HTP-c) | **HTP-nc**=Potential Comparative Toxic Unit for humans (HTP-nc) | **SQP**=Potential soil quality index (SQP)



## 5 Results

Abbr.	Unit	A1	A2	A3	A1- A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
SQP	Pt	2.25E+4	6.23E+2	2.40E+4	4.71E+4	2.68E+3	1.59E+3	0.00E+0	1.64E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.01E+0	7.76E+1	4.63E+2	1.18E+2	-1.23E+4

**PM**=Potential incidence of disease due to PM emissions (PM) | **IR**=Potential Human exposure efficiency relative to U235 (IRP) | **ETP-fw**=Potential Comparative Toxic Unit for ecosystems (ETP-fw) | **HTP-c**=Potential Comparative Toxic Unit for humans (HTP-c) | **HTP-nc**=Potential Comparative Toxic Unit for humans (HTP-nc) | **SQP**=Potential soil quality index (SQP)

### CLASSIFICATION OF DISCLAIMERS TO THE DECLARATION OF CORE AND ADDITIONAL ENVIRONMENTAL IMPACT INDICATORS

ILCD classification	Indicator	Disclaimer
ILCD type / level 1	Global warming potential (GWP)	None
	Depletion potential of the stratospheric ozone layer (ODP)	None
	Potential incidence of disease due to PM emissions (PM)	None
ILCD type / level 2	Acidification potential, Accumulated Exceedance (AP)	None
	Eutrophication potential, Fraction of nutrients reaching freshwater end compartment (EP-freshwater)	None
	Eutrophication potential, Fraction of nutrients reaching marine end compartment (EP-marine)	None
	Eutrophication potential, Accumulated Exceedance (EP-terrestrial)	None
	Formation potential of tropospheric ozone (POCP)	None
	Potential Human exposure efficiency relative to U235 (IRP)	1
	Abiotic depletion potential for non-fossil resources (ADP-minerals&metals)	2
ILCD type / level 3	Abiotic depletion potential for fossil resources (ADP-fossil)	2
	Water (user) deprivation potential, deprivation-weighted water consumption (WDP)	2
	Potential Comparative Toxic Unit for ecosystems (ETP-fw)	2
	Potential Comparative Toxic Unit for humans (HTP-c)	2
	Potential Comparative Toxic Unit for humans (HTP-nc)	2
	Potential Soil quality index (SQP)	2
<b>Disclaimer 1</b> – This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.		
<b>Disclaimer 2</b> – The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator.		

## 5 Results

### 5.2 INDICATORS DESCRIBING RESOURCE USE AND ENVIRONMENTAL INFORMATION BASED ON LIFE CYCLE INVENTORY (LCI)

#### PARAMETERS DESCRIBING RESOURCE USE

Abbr.	Unit	A1	A2	A3	A1- A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ	6.23E+3	1.56E+1	4.29E+3	1.05E+4	5.64E+1	3.23E+2	0.00E+0	7.74E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.30E-1	1.39E+0	5.80E+1	1.75E+0	-1.94E+3
PERM	MJ	0.00E+0	0.00E+0	8.36E+2	8.36E+2	0.00E+0	2.51E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
PERT	MJ	6.23E+3	1.56E+1	5.12E+3	1.14E+4	5.64E+1	3.48E+2	0.00E+0	7.74E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.30E-1	1.39E+0	5.80E+1	1.75E+0	-1.94E+3
PENRE	MJ	4.44E+4	1.02E+3	1.20E+4	5.74E+4	3.57E+3	1.94E+3	0.00E+0	1.09E+2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.93E+1	9.85E+1	5.51E+2	5.73E+1	-1.08E+4
PENRM	MJ	6.57E+3	0.00E+0	4.15E+2	6.99E+3	0.00E+0	2.10E+2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	-8.59E+1
PENRT	MJ	5.09E+4	1.02E+3	1.25E+4	6.44E+4	3.57E+3	2.15E+3	0.00E+0	1.09E+2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.93E+1	9.85E+1	5.51E+2	5.73E+1	-1.09E+4
SM	Kg	1.79E+2	0.00E+0	7.17E+0	1.86E+2	0.00E+0	5.59E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
RSF	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
NRSF	MJ	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
FW	m³	5.39E+1	1.51E-1	6.83E+0	6.09E+1	5.37E-1	1.93E+0	0.00E+0	7.22E-2	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.85E-3	2.38E-2	5.46E-1	5.60E-2	-1.19E+1

**PERE**=Use of renewable primary energy excluding renewable primary energy resources used as raw materials | **PERM**=Use of renewable primary energy resources used as raw materials | **PERT**=Total use of renewable primary energy resources | **PENRE**=Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials | **PENRM**=Use of non-renewable primary energy resources used as raw materials | **PENRT**=Total use of non-renewable primary energy resources | **SM**=Use of secondary material | **RSF**=Use of renewable secondary fuels | **NRSF**=Use of non-renewable secondary fuels | **FW**=Net use of fresh water

#### OTHER ENVIRONMENTAL INFORMATION DESCRIBING WASTE CATEGORIES

Abbr.	Unit	A1	A2	A3	A1- A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
HWD	Kg	2.11E+0	5.78E-3	7.12E-1	2.83E+0	2.25E-2	1.25E-1	0.00E+0	1.32E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	1.39E-3	6.27E-4	1.37E+0	2.63E-4	1.58E+0
NHWD	Kg	8.69E+2	5.00E+1	5.29E+1	9.72E+2	2.25E+2	1.60E+2	0.00E+0	6.32E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	8.99E-2	6.50E+0	1.07E+2	2.00E+2	-2.76E+2
RWD	Kg	8.41E-2	1.13E-3	1.13E-1	1.99E-1	1.20E-3	6.14E-3	0.00E+0	2.52E-4	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	5.35E-6	2.25E-5	1.04E-3	2.90E-5	-8.05E-3

**HWD**=Hazardous waste disposed | **NHWD**=Non-hazardous waste disposed | **RWD**=Radioactive waste disposed

## 5 Results

### ENVIRONMENTAL INFORMATION DESCRIBING OUTPUT FLOWS

Abbr.	Unit	A1	A2	A3	A1- A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
CRU	Kg	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
MFR	Kg	0.00E+0	0.00E+0	1.15E+1	1.15E+1	0.00E+0	9.06E+0	0.00E+0	5.28E-1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	2.81E+2	0.00E+0	6.03E+0
MER	Kg	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0
EET	MJ	0.00E+0	0.00E+0	2.92E+1	2.92E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	7.67E+2
EEE	MJ	0.00E+0	0.00E+0	1.70E+1	1.70E+1	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	0.00E+0	4.45E+2

**CRU**=Components for re-use | **MFR**=Materials for recycling | **MER**=Materials for energy recovery | **EET**=Exported Energy, Thermic | **EEE**=Exported Energy, Electric

## 5 Results

### 5.3 INFORMATION ON BIOGENIC CARBON CONTENT PER PIECE

#### BIOGENIC CARBON CONTENT

The following Information describes the biogenic carbon content in (the main parts of) the product at the factory gate per piece:


Biogenic carbon content	Amount	Unit
Biogenic carbon content in the product	0	kg C
Biogenic carbon content in accompanying packaging	27.18	kg C

#### UPTAKE OF BIOGENIC CARBON DIOXIDE

The following amount of carbon dioxide uptake is taken into account. Related uptake and release of carbon dioxide in downstream processes are not taken into account in this number although they do appear in the presented results. One kilogram of biogenic Carbon content is equivalent to 44/12 kg of biogenic carbon dioxide uptake.

Uptake Biogenic Carbon dioxide	Amount	Unit
Packaging	99.65	kg CO2 (biogenic)

## 6 Interpretation of results



- Modules A1 (Raw material supply) and A3 (Manufacturing) are the main contributors to most environmental impact categories, particularly in global warming potential (GWP) and acidification potential (AP).
- For GWP-luluc (land use and land use change), there is a large negative contribution from A3, likely associated with biogenic carbon uptake during manufacturing or use of biogenic materials.
- Module D consistently shows negative values, reflecting benefits from recycling or energy recovery beyond the system boundary.

## 7 References

### ISO 14040

ISO 14040:2006-10, Environmental management - Life cycle assessment - Principles and framework; EN ISO 14040:2006

### ISO 14044

ISO 14044:2006-10, Environmental management - Life cycle assessment - Requirements and guidelines; EN ISO 14044:2006

### ISO 14025

ISO 14025:2011-10, Environmental labels and declarations — Type III environmental declarations — Principles and procedures

### EN 15804+A2

EN 15804:2012+A2:2019/AC:2021, Sustainability of Buildings - Environmental Product Declarations - Framework Development Rules by Product Category

### EN 50693

Product category rules for life cycle assessments of electronic and electrical products and systems

### EPDItaly007

Core Product Category Rules based on EN 50693 for electrical and electronic products Rev. 3.1 (2024-11-12)

### EPDItaly 010

PCR Part B for insulator. REV. 1 ( 01-07-2024)

### Grid Solutions NT312440 (14.10.2022)

Harmonized standard document NT312440

### Kiwa-EE GPI R.2.0

Kiwa-Ecobility Experts, General Programme Instructions “Product Level”, SOP EE 1203\_R. 2.0 (27.02.2025)

### Kiwa-EE GPI R.2.0 Annex B1

Kiwa-Ecobility Experts, General Programme Instructions “Product Level” – Annex B1 Environmental Information Programme according to EN 15804 / ISO 21930, SOP EE 1203\_R. 2.0 (27.02.2025)

### Ecoinvent

ecoinvent Version 3.9.1 (December 2022)

### R<THINK characterization method

ecoinvent 3.9.1: EN 15804+A1 indicators (CML-IA Baseline v3.09), EN 15804+A2 indicators (EF 3.1)

## 7 References

### **IEC TS 62271-320:2025**

High-voltage switchgear and controlgear - Part 320: Environmental aspects and life cycle assessment rules for high-voltage switchgear and controlgear

### **PEFCRs**

Product Environmental Footprint Category Rules (PEFCRs) for Products in building, 2019

### **IEC/TR 62635**

Guidelines for end-of-life information provided by manufacturers and recyclers and for recyclability rate calculation of electrical and electronic equipment.



## 8 Contact information

Publisher	Operator	Owner of declaration
		
<b>Kiwa-Ecobility Experts</b> Wattstraße 11-13 13355 Berlin, DE	<b>Kiwa-Ecobility Experts</b> Wattstraße 11-13 13355 Berlin, DE	<b>Grid Solutions</b> 167 QUAI de la bataille de stalingrad 92130 Issy-les-Moulineaux , FR
<b>E-mail:</b> DE.Ecobility.Experts@kiwa.com <b>Website:</b> <a href="https://www.kiwa.com/de/en/themes/ecobility-experts/ecobility-experts-epd-program/">https://www.kiwa.com/de/en/themes/ecobility-experts/ecobility-experts-epd-program/</a>	<b>E-mail:</b> DE.Ecobility.Experts@kiwa.com <b>Website:</b> <a href="https://www.kiwa.com/de/en/themes/ecobility-experts/ecobility-experts-epd-program/">https://www.kiwa.com/de/en/themes/ecobility-experts/ecobility-experts-epd-program/</a>	<b>E-mail:</b> Solene.Michaud@gevernova.com <b>Website:</b> <a href="http://www.gevernova.com/grid-solutions">www.gevernova.com/grid-solutions</a>

Kiwa-Ecobility Experts is established member of the 